


AOQ Specifications 声光Q开关产品规格书 Q0041-QL068-025-1880



1. SPECIFICATIONS (规格)

Interaction material (介质材料)	Crystal quartz (石英)
Acoustic mode (声波模式)	Longitudinal (纵波)
Operating wavelength (工作波长)	1880 nm
Polarization (光偏振)	Linear, vertical to base (线偏振, 垂直于基座)
Transmission (透过率)	> 99.6%
Active aperture (有效孔径)	2.5 mm
Center frequency (中心频率)	68 MHz
Loss modulation (损耗调制)	> 85%
RF power (射频功率)	50W (max)
Input impedance (输入阻抗)	50Ω Nominal
VSWR (驻波比) @Fc	< 1.2:1
RF connector (射频接头)	BNC-F
Water flow rate (水流量)	> 1.4L/minute
Cooling (散热方式)	Water-cooling (水冷散热)
Shell material (外壳材料)	Aluminum alloy (铝合金)
Water cooling channel material (水冷块材料)	Stainless steel (不锈钢)

2. PERFORMANCE vs. WAVELENGTH (性能 vs. 波长)

Wavelength (光波长) -nm	1880
Bragg angle (布拉格角) -mrad	11.1
Separation angle (分离角) -mrad	22.2


3. ESTIMATED PERFORMANCE vs. BEAM DIAMETER (预估性能 vs. 光束直径)

Beam diameter (光束直径) -mm	1	2	2.5
Risetime (上升沿时间) -ns	113	226	282.5
Loss modulation (损耗调制)	85%	85%	85%

4. ORDERING CODES (编码规则)

	Materials		Acoustic type		Fc	Active aperture		Wavelength		
Q0001	—	X		X	XXX	—	XXX	—	XXXX	
	QZ	Q	Longitudinal	L	27.12 MHz	027	040	4 mm	1030	1030 nm
	TeO ₂	T	Shear	S	40.68 MHz	041	060	6 mm	1064	1064 nm
	Ge	G			80 MHz	080	080	8 mm	9600	9600 nm

5. DIMENSIONS (外形尺寸-mm)



6. SUGGESTED RF DRIVER ELECTRONICS (建议驱动型号)

RD1019-068-24-050-SZ

7. REVISION (版本)

Number (版本号)	Revisions date (修订日期)	Revision (修改项目)	Revision description (修订内容说明)
A	2024.8.29	NEW	NEW

Quality Assured: In house made, high damage threshold, Vacuum bonding, 100% Diffraction efficiency test & burn-in test.