

95mmAPO长工作距离金相物镜

产品参数

型号	类型	数值孔径	工作距离	焦距	管镜	视场直径目镜	视场直径相机	分辨率	焦深	螺纹	长度	直径
MODEL	TYPE	N.A	W.D (mm)	FL (mm)	TL (mm)	25OFN (mm)	1" 相机	RES (μm)	DOF±Δ (μm)	SCREW	Length (mm)	Dia. (mm)
M Plan APO 2X	BF	0.055	34	100	F=200	12	4.8x6.4	5	91	M26	66.5	34
M Plan APO 5X	BF	0.15	44.9	40	F=200	4.8	1.92X2.56	2.5	14	M26	55.65	34
M Plan APO 10X	BF	0.30	33.9	20	F=200	2.4	0.96X1.28	1	3.5	M26	66.6	34
M Plan APO 20X	BF	0.45	20.1	10	F=200	1.2	0.48X0.64	0.7	1.55	M26	80.45	34
M Plan APO 50X	BF	0.65	9.4	4	F=200	0.5	0.19X0.26	0.4	0.61	M26	91.1	34
M Plan APO 20X ELWD	BF	0.30	30.9	10	F=200	1.2	0.48X0.64	1	3.2	M26	69.65	34
M Plan APO 50X ELWD	BF	0.45	20.1	4	F=200	0.5	0.19X0.26	0.7	0.9	M26	80.45	34
M Plan APO 100X	BF	0.80	6.0	2	F=200	0.24	0.1X0.13	0.4	0.4	M26	94.5	36

